



**SPECIFICATIONS :**

1. RATING : DC 3V , 120mA
2. INTER – CONTACT RESISTANCE : 100m OHM MAX. AT BOTH THE POSITIVE AND NEGATIVE TERMINALS WHEN MEASURED BETWEEN THE TERMINALS OF THE CR2032 AT 1KHz WITH LOW DRAINAGE ( 100mA MAX. )
3. INSULATION RESISTANCE : 100M OHM MIN. WITH DC 500V APPLIED BETWEEN THE POSITIVE AND NEGATIVE TERMINALS.
4. VOLTAGE DURABILITY : NO DEGRADATION WITH DC 500V APPLIED FOR ONE MINUTE BETWEEN THE POSITIVE AND NEGATIVE TERMINALS.
5. Unless other specified, tolerance is  $\pm 0.2$ mm

3.	NEGATIVE CONTACT	1	STAINLESS STEEL 301	TIN	0.15 t
2.	POSITIVE CONTACT	1	STAINLESS STEEL 301	TIN	0.15 t
1.	HOUSING	1	Liquid Crystal Polymer	L.C.P	UL94V-0
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS
VERSION	APPROVAL BY	CHECKED BY	DRAWD BY	UNITS	
A2				lo 2009.08.25	mm
REVISION	PROJECTION	PRODUCT	DRAWING NO.	SCALE	
		BATTERY HOLDER	BH-004-LCP	5/1	
			UNITOP ELECTRONICS CO., LTD.		